

Town of Livonia Ambulance District #1

Specifications for EMS turnout gear

Compliance

- 1) It must be NFPA 1999 compliant

Material

- 1) The outer shell is to be constructed of NOMEX IIIA treated with a Super Shelltite water repellent finish.
- 2) The inner shell shall be CROSSTECH EMS fabric.
- 3) All seams in the liner shall be sealed with GORE-SEAM tape.
- 4) The shell liner shall be constructed of a pill-resistant fleece.
- 5) Trim shall be sewn TrimTrax Thread protection System.

Jacket

- 1) It shall have a full length zipper including collar with a double storm flap front enclosure.
- 2) It shall have 2 lower cargo pockets with integral hand warmers pockets built in.
- 3) It shall have side zippers to allow access to belt mounted equipment.
- 4) 2" triple trim 3M scotchlite color Lime-Yellow

Pants

- 1) It shall have a free hanging liner system.
- 2) It shall have reinforced knee pads.
- 3) It shall have an elasticized waist with a quick adjust draw cord.
- 4) It shall have 2 bellows pockets 1 on each thigh.
- 5) It shall have leg zippers to allow for boot access.
- 6) 2" triple trim 3M scotchlite color Lime - Yellow

Options

- 1) Position of all options to be decided at time of order.
- 2) Radio pocket 2"x3"x8.5"
- 3) Belt loops and Kevlar belt
- 4) Lettering (LIVONIA EMS) on back of jacket
- 5) Star of life